



**University of  
Zurich**<sup>UZH</sup>

**Zurich Open Repository and  
Archive**

University of Zurich  
University Library  
Strickhofstrasse 39  
CH-8057 Zurich  
[www.zora.uzh.ch](http://www.zora.uzh.ch)

---

Year: 2014

---

## **From airborne laser scanning intensity to a distributed glacier surface albedo product**

Joerg, Philip C ; Weyermann, Jörg ; Morsdorf, Felix ; Zemp, Michael ; Schaepman, Michael E

Posted at the Zurich Open Repository and Archive, University of Zurich

ZORA URL: <https://doi.org/10.5167/uzh-100982>

Conference or Workshop Item

Published Version

Originally published at:

Joerg, Philip C; Weyermann, Jörg; Morsdorf, Felix; Zemp, Michael; Schaepman, Michael E (2014). From airborne laser scanning intensity to a distributed glacier surface albedo product. In: European Geosciences Union General Assembly 2014, Vienna, Austria, 27 April 2014 - 2 May 2014. Copernicus Publications, 3401.



## **From airborne laser scanning intensity to a distributed glacier surface albedo product**

Philip C. Joerg, Jörg Weyermann, Felix Morsdorf, Michael Zemp, and Michael E. Schaepman  
Department of Geography, University of Zurich, Zurich, Switzerland

In recent years, multi-temporal topographic measurements from airborne laser scanning (ALS) have been increasingly used as an accurate information source to calculate geodetic glacier mass balances. Simultaneously to collecting topographic data, most ALS instruments record the reflected signal intensity for each laser emission and therefore provide additional information on the reflectance characteristics of the scanned surface. Along with air temperature, the surface albedo of snow and ice was identified as a major driving factor of glacier melt. Consequently, better knowledge on glacier albedo could substantially improve energy balance based glacier melt modeling.

In this study, we collected on-glacier spectro-radiometric and albedometer measurements to serve as ground reference to radiometrically calibrate high resolution ALS intensity data into a distributed albedo map. This method resulted in albedo values between 0.5 on the glacier tongue and 0.9 on fresh snow in high altitudes with 99.6% of all albedo values falling within the albedo boundary conditions, i.e. values between 0 and 1. Corrected ALS intensity data provided distributed albedo products which allow simulating albedo in glacier energy and mass balance models more realistically. Remaining challenges are the coarse intensity sampling interval of the ALS system, an insufficient correction of the snow bidirectional reflectance distribution function (BRDF) resulting in a striped pattern in the albedo map, and the physical linking of narrow to broad band albedo.